

Applic. No. 10/695,365

Amdt. dated January 9, 2006

Reply to Office action of September 7, 2005

Claim Amendments

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Claim 1 (currently amended): An apparatus for controlling a temperature of a printing plate in an external drum exposer having an exposure drum for holding the printing plate, the apparatus comprising:

an internal pipe ~~disposed on~~ having a longitudinal axis disposed coaxially with an axis of the exposure drum; and

at least one rotary lead-through fluidically communicating with ~~and through which a temperature controlled liquid flows into~~ said internal pipe for feeding a temperature-controlled liquid into said internal pipe, thereby achieving a defined temperature of the printing plate.

Claim 2 (original): The apparatus according to claim 1, further comprising webs connected to said internal pipe, the exposure drum is a cylinder connected to said internal pipe by said webs.

Applic. No. 10/695,365

Amdt. dated January 9, 2006

Reply to Office action of September 7, 2005

Claim 3 (original): The apparatus according to claim 2, wherein the cylinder, said internal pipe and said webs are fabricated from a thermally conductive material.

Claim 4 (original): The apparatus according to claim 2, wherein the cylinder, said internal pipe and said webs are fabricated from an extruded part.

Claim 5 (original): The apparatus according to claim 1, wherein said rotary lead-through is disposed at a first end of the exposure drum with which the temperature-controlled liquid is led into said internal pipe; and

further comprising a further rotary lead-through disposed at a second end of the exposure drum with which the temperature-controlled liquid is led out of said internal pipe.

Claim 6 (original): The apparatus according to claim 1, wherein said rotary lead-through is a two-way rotary lead-through disposed at one end of the exposure drum, said two-way rotary lead-through leading the temperature-controlled liquid into and out of said internal pipe.

Claim 7 (original): The apparatus according to claim 1, further comprising a temperature control unit disposed in a

Applic. No. 10/695,365

Amdt. dated January 9, 2006

Reply to Office action of September 7, 2005

path of the temperature-controlled liquid for keeping the
temperature-controlled liquid at a constant temperature.

Claim 8 (original): The apparatus according to claim 1,
wherein the temperature-controlled liquid is water.

Claim 9 (original): The apparatus according to claim 8,
wherein the temperature-controlled liquid further contains at
least one of a corrosion-prevention additive and an antifreeze
additive.

Claim 10 (original): The apparatus according to claim 3,
wherein said thermally conductive material is aluminum.

Claim 11 (cancelled).

Claim 12 (currently amended): An exposer for controlling a
temperature of a printing plate, comprising:

an exposure head for exposing the printing plate;

an exposure drum for holding the printing plate and having an
axis;

Applic. No. 10/695,365

Amdt. dated January 9, 2006

Reply to Office action of September 7, 2005

an internal pipe ~~disposed along~~ having a longitudinal axis
disposed coaxially with said axis of said exposure drum; and

at least one rotary lead-through fluidically communicating
with ~~and through which a temperature-controlled liquid flows~~
~~into~~ said internal pipe for feeding a temperature-controlled
liquid into said internal pipe, thereby achieving a defined
temperature of the printing plate.

Claim 13 (currently amended): An exposser for controlling a
temperature of a printing plate, comprising:

an exposure head for exposing the printing plate;

an exposure body for holding the printing plate and having an
axis;

an internal pipe ~~disposed along~~ having a longitudinal axis
disposed coaxially with said axis of said exposure body; and

at least one rotary lead-through fluidically communicating
with ~~and through which a temperature-controlled liquid flows~~
~~into~~ said internal pipe for feeding a temperature-controlled
liquid into said internal pipe, thereby achieving a defined
temperature of the printing plate.

Applic. No. 10/695,365

Amdt. dated January 9, 2006

Reply to Office action of September 7, 2005

Claim 14 (currently amended): An exposure drum for
controlling a temperature of a printing plate, comprising:

an a cylindrical body for holding the printing plate and
having an axis;

an internal pipe ~~disposed along~~ having a longitudinal axis
disposed coaxially with said axis of said cylindrical body;
and

at least one rotary lead-through fluidically communicating
with ~~and through which a temperature controlled liquid flows~~
~~into~~ said internal pipe for feeding a temperature-controlled
liquid into said internal pipe, thereby achieving a defined
temperature of the printing plate.

Claim 15 (new). The apparatus according to claim 1, wherein
the defined temperature of the printing plate is maintained
irrespective of an ambient temperature.

Claim 16 (new). The apparatus according to claim 2, wherein
said webs are longitudinal webs running along the axis of the
exposure drum over substantially an entire length of the
exposure drum.